

ULIST / URBAN STEP LIGHTS

FEATURES

- IP44
- >50,000 Lifetime Hours
- White Gloss Finish with Square Corners
- 3 CCT Colour Temperature



ULIST - LUM URBAN STEP LIGHT

Power	3W
Lumen Output	56lm
Input Voltage	220-240V AC
Efficacy	20lm/W
Beam Angle	90°
Color Temperature	3000K, 4000K, 5700K
CRI	>80
ICF/ IC-4 Tested	Yes
Approvals & Certificates	SAA
Operating Temperature	-20°C to +40°C
Class	Class 2
IP Rating	IP44 (Front Only)
Dimming	Yes
LED Lifetime	>50,000hrs
Material	Polycarbonate
DIMENSIONS	
Fascia Size (HxW)	116 x 78mm
Fitting Size (LxWxD)	108 x 56 x 56.8mm

ULISTBBM / URBAN STEP LIGHTS

FEATURES

- IP44
- >50,000 Lifetime Hours
- Black Metal Finish with Square Corners
- 3 CCT Colour Temperature



ULISTBBM - LUM URBAN STEP LIGHT BLK BLK METAL

Power	3W
Lumen Output	18lm
Input Voltage	220-240V AC
Efficacy	6lm/W
Beam Angle	90°
Color Temperature	3000K, 4000K, 5700K
CRI	>80
ICF/ IC-4 Tested	Yes
Approvals & Certificates	SAA
Operating Temperature	-20°C to +40°C
Class	Class 2
IP Rating	IP44 (Front Only)
Dimming	Yes
LED Lifetime	>50,000hrs
Material	Polycarbonate
DIMENSIONS	
Fascia Size (HxW)	116 x 78mm
Fitting Size (LxWxD)	108 x 56 x 56.8mm

ULISTWSM / URBAN STEP LIGHTS

FEATURES

- IP44
- >50,000 Lifetime Hours
- Silver Metal Finish with Square Corners
- 3 CCT Colour Temperature



ULISTWSM - LUM URBAN STEP LIGHT WHT SLVR METAL

Power	3W
Lumen Output	38lm
Input Voltage	220-240V AC
Efficacy	13lm/W
Beam Angle	90°
Color Temperature	3000K, 4000K, 5700K
CRI	>80
ICF/ IC-4 Tested	Yes
Approvals & Certificates	SAA
Operating Temperature	-20°C to +40°C
Class	Class 2
IP Rating	IP44 (Front Only)
Dimming	Yes
LED Lifetime	>50,000hrs
Material	Polycarbonate
DIMENSIONS	
Fascia Size (HxW)	116 x 78mm
Fitting Size (LxWxD)	108 x 56 x 56.8mm